



# TELSMITH

an Astec Industries Co.

**Telsmith Incorporated**

10910 N. Industrial Drive

Mequon WI. 53092

Parts Toll Free: 1-800-688-6601

www.telsmith.com

## LUBRICANT RECOMENDATIONS FOR JAW CRUSHERS

Lubricant Type	Ambient Temperature °F/(°C)	Specification	Recommended Standard Lubricant	Recommended Synthetic Lubricant
Grease	Below 40°F/(4°C) with Central Grease System	NLGI 00, with EP Additives	--	Mobilith SHC 007
	Below 100°F (Below 38°C)	NLGI 2, with EP Additives	Mobil Delvac Xtreme Service Grease	Mobilith SHC 460
	Above 100°F (Above 38°C)	NLGI 2, with EP Additives	--	Mobilith SHC 460
Lube Oil	Below 40°F (Below 4°C)	ISO 100, AGMA 3 EP	Mobilgear 600 XP 100	Mobilgear SHC 150
	Above 40°F (Above 4°C)	ISO 150, AGMA 4 EP	Mobilgear 600 XP 150	Mobilgear SHC 150
Hydraulic Oil	Below 40°F (Below 4°C)	ISO 32 HVI AW Low Pour Point	Mobil DTE 10 Excel 32	Mobil SHC 524
	Above 40°F (Above 4°C)	ISO 68, Antiwear	Mobil DTE 26 or Mobil DTE 10 Excel 68	Mobil SHC 526

**\*\*CONSULT YOUR OWNERS MANUAL FOR CHANGE/REPLENISHMENT INTERVAL\*\***

For Mobil Product Information call 1-800-662-4525, or visit [www.mobilindustrial.com](http://www.mobilindustrial.com)