



# TELSMITH

an Astec Industries Co.

## Telsmith Incorporated

10910 N. Industrial Drive

Mequon WI. 53092

Parts Toll Free: 1-800-688-6601

[www.telsmith.com](http://www.telsmith.com)

### LUBRICANT RECOMENDATIONS FOR CONE CRUSHERS

Lubricant Type	Ambient Temp °F/(°C)	Specification	Recommended Standard Lubricant	Recommended Synthetic Lubricant
Lube Oil	Below 40°F (Below 4°C)	ISO 100, AGMA 3 EP	Mobilgear 600 XP 100	Mobilgear SHC 100
	40°F to 80°F (4°C to 27°C)	ISO 150, AGMA 4 EP	Mobilgear 600 XP 150	Mobilgear SHC 150
	Above 80°F (Above 27°C)	ISO 220, AGMA 5 EP	Mobilgear 600 XP 220	Mobilgear SHC 220
Hydraulic Oil	Below 40°F (Below 4°C)	ISO 32, HVI AW Low Pour Point	Mobil DTE 10 Excel 32	Mobil SHC 524
	Above 40°F (Above 4°C)	ISO 68, Antiwear	Mobil DTE 26 or Mobil DTE 10 Excel 68	Mobil SHC 526
Buttress Thread Grease	All Temperatures	NGLI 2, with EP Additives, 3% Moly (min.)	Mobilgrease XHP 322 Mine	-

**\*\* CONSULT YOUR OWNERS MANUAL FOR CHANGE/REPLENISHMENT INTERVAL \*\***

For Mobil Product Information call 1-800-662-4525, or Visit [www.mobilindustrial.com](http://www.mobilindustrial.com)